



Stainless Steel Liquid Tight Strain Relief Fittings (303) INOX - NPT Threads



High Performance, High/Low Temperatures & Corrosion Resistant

Part Numbers		Cable Range Inches (mm)	Thread Type & Size See page 49 for thread specs	Dimensions in Inches (mm)			
Standard  Has a Buna-N (NBR) Insert	PVDF  Has a Viton® Insert			A Clearance Hole + .01" + .25 mm	B Body Length	D Thread Length	F ₁ /F Wrench Flats
CD07AA-SS	CD07AA-SV	.12 - .26 (3 - 6.5)	PG 7	.49 (12.5)	.75 (19)	.20 (5)	.55 (14)
CD07AR-SS	CD07AR-SV	.08 - .20 (2 - 5)					
CD09AA-SS	CD09AA-SV	.16 - .31 (4 - 8)	PG 9	.60 (15.2)	.83 (21)	.24 (6)	.67 (17)
CD09AR-SS	CD09AR-SV	.08 - .24 (2 - 6)					
CD11AA-SS	CD11AA-SV	.20 - .39 (5 - 10)	PG 11	.73 (18.5)	.87 (22)	.24 (6)	.87 (22)
CD11AR-SS	CD11AR-SV	.12 - .28 (3 - 7)					
CD13AA-SS	CD13AA-SV	.24 - .47 (6 - 12)	PG 13 / 13.5	.80 (20.3)	.94 (24)	.26 (6.5)	.87 (22)
CD13AR-SS	CD13AR-SV	.20 - .35 (5 - 9)					
CD16AA-SS	CD16AA-SV	.39 - .55 (10 - 14)	PG 16	.89 (22.5)	.91 (23)	.26 (6.5)	.94 (24)
CD16AR-SS	CD16AR-SV	.28 - .47 (7 - 12)					
CD21AA-SS	CD21AA-SV	.51 - .71 (13 - 18)	PG 21	1.12 (28.4)	.94 (24)	.28 (7)	1.18 (30)
CD21AR-SS	CD21AR-SV	.35 - .63 (9 - 16)					
CD29AA-SS	CD29AA-SV	.71 - .98 (18 - 25)	PG 29	1.47 (37.3)	1.14 (29)	.31 (8)	1.61 (41)
CD29AR-SS	CD29AR-SV	.51 - .79 (13 - 20)					
CD36AA-SS	CD36AA-SV	.87 - 1.26 (22 - 32)	PG 36	1.85 (47)	1.38 (35)	.31 (8)	1.97 (50)
CD36AR-SS	CD36AR-SV	.79 - 1.02 (20 - 26)					
CD12MA-SS	CD12MA-SV	.12 - .26 (3 - 6.5)	M12 x 1.5	.47 (12)	.75 (19)	.26 (6.5)	.55 (14)
CD12MR-SS	CD12MR-SV	.08 - .20 (2 - 5)	M16 x 1.5	.63 (16)	.87 (22)	.24 (6)	.87 (22)
CD16MA-SS	CD16MA-SV	.20 - .39 (5 - 10)					
CD16MR-SS	CD16MR-SV	.12 - .28 (3 - 7)	M20 x 1.5	.79 (20)	.91 (23)	.24 (6)	.94 (24)
CD20MA-SS	CD20MA-SV	.39 - .55 (10 - 14)					
CD20MR-SS	CD20MR-SV	.28 - .47 (7 - 12)	M25 x 1.5	.98 (25)	.94 (24)	.28 (7)	1.18 (30)
CD25MA-SS	CD25MA-SV	.51 - .71 (13 - 18)					
CD25MR-SS	CD25MR-SV	.35 - .63 (9 - 16)	M32 x 1.5	1.26 (32)	1.14 (29)	.31 (8)	1.61 (41)
CD32MA-SS	CD32MA-SV	.71 - .98 (18 - 25)					
CD32MR-SS	CD32MR-SV	.51 - .79 (13 - 20)	M40 x 1.5	1.57 (40)	1.38 (35)	.31 (8)	1.97 (50)
CD40MA-SS	CD40MA-SV	.87 - 1.26 (22 - 32)					
CD40MR-SS	CD40MR-SV	.79 - 1.02 (20 - 26)					


316 INOX Stainless Steel also available in NPT Threads upon request

*Note: VDE Approval only applies to Fittings with Metric Thread.

Stainless Steel Strain Relief Fittings can be used in many applications, where the environment dictates a corrosion proof solution.

Typical applications include:

- Off-shore
- Marine
- Chemical Plants
- Food Processing
- Clean Room
- Other Rugged Applications



Stainless Steel (303), Nickel Plated Brass & Nylon Locking Nuts and Other Accessories available on page 28 & 29.



Suggested Clearance Hole for Non-Threaded Mounting



Dome Fittings also available with the following approvals:



Stainless Steel Liquid Tight Strain Relief Fittings (316) INOX - NPT Threads



High Performance, High/Low Temperatures & Corrosion Resistant

Part Numbers		Cable Range Inches (mm)	Thread Type & Size See page 49 for thread specs	Dimensions in Inches (mm)			
Standard  Has a Buna-N (NBR) Insert	PVDF  Has a Viton® Insert			A Clearance Hole + .01" + .25 mm	B Body Length	D Thread Length	F ₁ /F Wrench Flats
CD09NA-6S	CD09NA-6V	.16 - .31 (4 - 8)	3/8" NPT	.68 (17.2)	.83 (21)	.59 (15)	.67 (17) / .75 (19)
CD09NR-6S	CD09NR-6V	.08 - .24 (2 - 6)					
CD13NA-6S	CD13NA-6V	.24 - .47 (6 - 12)	1/2" NPT	.83 (21.1)	.94 (24)	.51 (13)	.87 (22) / .94 (24)
CD13NR-6S	CD13NR-6V	.20 - .35 (5 - 9)					
CD21NA-6S	CD21NA-6V	.51 - .71 (13 - 18)	3/4" NPT	1.05 (26.7)	.98 (25)	.51 (13)	1.18 (30)
CD21NR-6S	CD21NR-6V	.35 - .63 (9 - 16)					
CD29NA-6S		.71 - .98 (18 - 25)	1" NPT	1.35 (34.3)	1.14 (29)	.75 (19)	1.57 (40)
CD29NR-6S		.51 - .79 (13 - 20)					

303 INOX Stainless Steel also available in PG and Metric Threads upon request

*Note: VDE Approval only applies to Fittings with Metric Thread.



The 316 material is much harder and ideal for direct exposure to salt water and chemical solutions in marine, off-shore, pharmaceutical, etc.



PVDF (Teflon®) Clamping Insert

For Material Specifications please refer to page 45.