



SEALCON

800-456-9012 / 303-699-1135
www.sealconusa.com/med

Two Outstanding Companies!
One Dependable Source!
Your Cable & Accessories Solution House!
We Provide Complete Solutions for your Application Needs!



HI-TECH CONTROLS, INC.

800-677-8942 / 303-680-5159
www.hitechcontrols.com/med



Servo Motors



Renewable Energy



Food & Beverage



High Temperature



Robotics



Petro-Chemical



Standard / Elongated / EMI & RFI / Armored / Non-Armored / Strain Relief, Cable Glands, Cord Grip
Materials: Nylon, Nickel Plated Brass, PVDF, Stainless Steel, Hazardous & Explosive etc.
Threads: NPT, Metric, PG & BSPP
Cable OD: 0.08 - 3.54" (2 - 90 mm)
Benefits: Large Inventory, Great Quality & Affordable Prices, V0 Rated, 2D/3D CAD!



- Interlocking Armor Cone
- Halogen / Phosphorous-Free
- Included: Silicone Seals & O-Rings
- Zero Torsion Cable Core/Armor, Dual Seal
- Fast/Easy Assembly with Max. Grip
- Temperature Range: -76°F - 221°F
- IP 68 (5 BAR), EN 60529

2D/3D CAD!



V0 Rated!

Featured Products

EXIOS Strain Relief Fittings, Cable Glands for Hazardous/Explosion Proof Areas

- Approvals: IECEx, ATEX, Ex-d / Ex-e / Ex-tD
- Zones: 1, 2, 20, 21 & 22
- Gas Groups: IIA, IIB & IIC – Apparatus Group III
- Equipment Protection Level GbDa
- Interlocking Armor Cone
- Halogen- & Phosphorous-free
- Included: Silicone Seals & O-Rings
- Zero Torsion on Cable Core & Armor, Dual Seal
- Fast & Easy Assembly with Maximum Grip
- Temperature Range: -76°F to 221°F (-60°C to +105°C)
- IP 68 (5 BAR), EN 60529



EXIOS

Unsurpassed Customer Service!

One-Stop Shopping!

No Minimum Orders!

Samples Available!

Call for a Catalog!



For more information call us or visit our website!

31,000+ Items in Stock!

\$35 Million Inventory!

Multi-Approved Tray Cable Traycontrol 600/600-C

- Flexible & Oil-Resistant / No Conduit Needed
- Approvals: UL, Type TC-ER, PLTC-ER, WTTTC, ITC-ER, CSA CIC/TC, MTW, CSA FT4, NFPA 79 Edition 2007
- Available gauges: 18 AWG to 500 MCM
- Applications: Plant Expansion, Contractor Market, A&E Firm Plant Designs, Renewable & Energy Tray Wiring



Intrinsically Safe Cable: OZ-BL, OZ-BL-CY & OB-BL-PAAR-CY

- Flexible Blue (RAL 5015) PVC Outer Jacket for Hazardous Areas
- Approvals: VDE, CE, PCT Gost
- Shield / Non-Shielded Versions, EMI Preferred Type
- Nominal Voltage: Uo/U 300/500/900 V
- Temperature Range: -40°F to +176°F (-40°C to +80°C)



Cables & Wires

One Stop Source for Wires & Cables!
Types: Control, Power, Hi-Flex, Track, High / Low Temp., Halogen-free, Servo, VFD, Robotic, Composite, Ribbon, Data (CAT), Single Conductor, Etc!
Approvals: UL, TC-ER & CSA CIC/TC, WTTTC, CSA FT4, NFPA 79 2007, CE, VDE, HAR, AWM, MTW, etc.



Camozzi Pneumatics

Fittings: Brass, Composite, Pro-Fit®
Valves: Manual, Mechanical, Air-Pilot & Flow Control Valves
Cylinders: Mini-Cylinders, Tie-Rod & Aluminum Profile Cylinders
FRL Units: Filters, Regulators & Lubricators



Solar / Photovoltaic Fittings Strain Relief Fittings, Cable Glands

- Black Dome & Flex (Only) UL f1 (746C), UV Stable & Meets Water / Immersion Requirements (Liquid Tight), IP 68 & 69K, NEMA 4x & 6, V0 Flame Rating
- Available Inserts: Standard, Reduced, Multi-Hole & Silicone

Our Service makes the Difference!

Conduit System

High Pull-Out Resistance, Robust Performance, Long Life Expectancy, Fast/Easy Installation, No Tools required!
Material: Nylon 6/6, NEMA 4, IP 54/65
Conduit: Standard and Super Flex Corrugated Conduit
Fittings: Push-in, Turn-to-Seal, Snapclick-DUO (Double-Sealed Combination Conduit & Cable Strain Relief Fittings, Flange / Bulkhead, Mounting Brackets



The Cable, Wire & Enclosure Experts!



Solar Plus Enclosures (UV-protected)



Industrial Enclosures

Materials: Polycarbonate, ABS, EMI, Polyester, Polystyrene, Aluminum, Powder-coated Steel, Stainless Steel.

Features: Square/rectangle shape, Solid & transparent lids, PG/Metric Knockouts or Smooth Walls, Flanges, Extension Frames, Hinges & Latches.
Applications: Indoor/Outdoor, Medical, Offshore, Marine, Wi-Fi, Hazardous Areas, Solar, etc.



Solar Enclosures