

No Limits

### IP 67 – liquid tight when disconnected



Using a rubber diaphragm makes this connector liquid tight either connected or disconnected (NEMA 4 = IP 67).

### Bulkhead Connector



Bulkhead connectors accept plugs on both sides. They are rugged, liquid tight and available in all number of poles.

### Simple EMI / RFI shielding



An integrated metalized EMI clamping insert grounds to the braid significantly simplifying the assembly of the elbow connector.

### MULTI Seal Connector



A large selection of standard MULTI seal inserts allow strain relief of several individual conductors on one single connector.

### Flexible Cable Protection



In addition to the integrated strain relief, the flex nut adds kink protection to a cable - available for all connector sizes.

### Adaptor flange



To secure loose connections, an adaptor flange can be attached to a straight connector.

### 12-point hex and knurled nut



This special nut makes connection simple by either tightening the connector manually (knurled nut) or with a wrench (12-point hex).

### Conduit Attachment



Flexible corrugated conduit can be attached to a connector with an adapter offering strain relief and cable protection as well.

## No Limits

### Connector with specific pull-out resistance



After reaching a certain pull-out force the connection releases preventing damage to the device (apparatus).

### Bulkhead Fitting



This fitting with oversized flange is commonly used in the ship building industry where Signal Connections have to be maintained under extreme conditions.

### Captive Protective Cap



The metal protective cap is secured to a cable by a safety ring and stays attached in open connections.

### ANACONDA Conduit Adapter



HUMMEL offers custom adapters for ANACONDA conduit systems in hazardous locations.

### Distribution-box



Distribution-boxes are known as important components for applications in automation. Robust and fully wired they are done according to customers specification.

### Coloured Overmould



Completing a design or showing technical functions, overmould could be made in different colours too (e.g. DESINA green RAL 6018).