

Nylon Liquid Tight Strain Relief Fittings Multi-Hole - PG Threads



Optional Locking Nuts,
O-Rings & Other
Accessories starting on
Page 29 - 40.



Multi-Hole Inserts are available in Silicone and FKM upon request.

Nylon Strain Relief

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)			Part Numbers of Inserts Only	
-40°F to 212°F (-40°C to 100°C)			No. of Holes	Diameter of Holes			
Black	Gray	See page 56 for thread specs		mm	Inches		
CD07AP-BK	CD07AP-GY		PG 7/14" NPT	Solid Insert			1.089.0799.19
CD09A1-BK	CD09A1-GY	PG 9	4	1.4	.06	1.089.0900.19	
CD09A2-BK	CD09A2-GY		2	3.0	.12	1.089.0901.19	
CD09A3-BK	CD09A3-GY		5	1.6	.06	1.089.0902.19	
CD09A4-BK	CD09A4-GY		2	1.7	.07	1.089.0903.19	
CD09A5-BK	CD09A5-GY		10	1.4	.06	1.089.0904.19	
CD09A6-BK	CD09A6-GY		6	1.4	.06	1.089.0905.19	
CD09A7-BK	CD09A7-GY		3	1.7	.07	1.089.0906.19	
CD09A8-BK	CD09A8-GY		4	1.7	.07	1.089.0907.19	
CD09A9-BK	CD09A9-GY		4	2.3	.09	1.089.0908.19	
CD09AP-BK	CD09AP-GY		Solid Insert		1.089.0999.19		
CD11A1-BK	CD11A1-GY		PG 11	2	3.0	.12	1.089.1100.19
CD11A2-BK	CD11A2-GY			3	3.0	.12	1.089.1101.19
CD11A3-BK	CD11A3-GY	2		4.0	.16	1.089.1102.19	
CD11A4-BK	CD11A4-GY	3		1.5	.06	1.089.1103.19	
CD11A5-BK	CD11A5-GY	4		2.8	.11	1.089.1104.19	
CD11AP-BK	CD11AP-GY	Solid Insert		1.089.1199.19			
CD13A1-BK	CD13A1-GY	PG 13 / 13.5	3	2.0	.08	1.089.1300.19	
CD13A2-BK	CD13A2-GY		6	3.0	.12	1.089.1301.19	
CD13A3-BK	CD13A3-GY		3	4.0	.16	1.089.1302.19	
CD13A4-BK	CD13A4-GY		2	5.0	.20	1.089.1303.19	
CD13A5-BK	CD13A5-GY		3	3.0	.12	1.089.1304.19	
CD13A6-BK	CD13A6-GY		2	5.2	.20	1.089.1305.19	
CD13A7-BK	CD13A7-GY		2	3.8	.15	1.089.1306.19	
CD13A8-BK	CD13A8-GY		2	4.2	.17	1.089.1307.19	
CD13A9-BK	CD13A9-GY		2	2.5	.10	1.089.1308.19	
CD13AP-BK	CD13AP-GY		Solid Insert		1.089.1399.19		
CD16A1-BK	CD16A1-GY		PG 16	3	3.0	.12	1.089.1600.19
CD16A2-BK	CD16A2-GY			3	4.0	.16	1.089.1601.19
CD16A3-BK	CD16A3-GY	4		4.0	.16	1.089.1602.19	
CD16A4-BK	CD16A4-GY	5		4.0	.16	1.089.1603.19	
CD16A5-BK	CD16A5-GY	6		4.0	.16	1.089.1604.19	
CD16A6-BK	CD16A6-GY	2		6.0	.24	1.089.1605.19	
CD16A7-BK	CD16A7-GY	3		5.6	.22	1.089.1606.19	
CD16A8-BK	CD16A8-GY	6		3.0	.12	1.089.1607.19	
CD16A9-BK	CD16A9-GY	*4		3.0	.12	*1.089.1610.19	
CD16A0-BK	CD16A0-GY	6		3.8	.15	1.089.1909.19	
CD16AP-BK	CD16AP-GY	Solid Insert		1.089.1699.19			

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)			Part Numbers of Inserts Only	
-40°F to 212°F (-40°C to 100°C)			No. of Holes	Diameter of Holes			
Black	Gray	See page 56 for thread specs		mm	Inches		
CD21A1-BK	CD21A1-GY		PG 21	4	6.0		.24
CD21A2-BK	CD21A2-GY	3		7.0	.28	1.089.2101.19	
CD21A3-BK	CD21A3-GY	2		8.0	.31	1.089.2102.19	
CD21A4-BK	CD21A4-GY	4		5.0	.20	1.089.2103.19	
CD21A5-BK	CD21A5-GY	1		8.0	.31	1.089.2104.19	
CD21A6-BK	CD21A6-GY	4		5.2	.20	1.089.2105.19	
CD21A7-BK	CD21A7-GY	3		5.2	.20	1.089.2106.19	
CD21A8-BK	CD21A8-GY	4 / 1		5.2/3.7	.20/.15	1.089.2107.19	
CD21A9-BK	CD21A9-GY	2		7.4	.29	1.089.2108.19	
CD21AP-BK	CD21AP-GY	Solid Insert		1.089.2199.19			
CD29A1-BK	CD29A1-GY	PG 29		6	6.5	.26	1.089.2900.19
CD29A2-BK	CD29A2-GY			4	9.0	.35	1.089.2901.19
CD29A3-BK	CD29A3-GY		4	9.5	.37	1.089.2902.19	
CD29A9-BK	CD29A9-GY		2	11.0	.43	1.089.2908.19	
CD29AP-BK	CD29AP-GY		Solid Insert		1.089.2999.19		
CD36A1-BK	CD36A1-GY	PG 36	5	9.0	.35	1.089.3600.19	
CD36A2-BK	CD36A2-GY		7	9.0	.35	1.089.3601.19	
CD36A3-BK	CD36A3-GY		6	8.0	.31	1.089.3602.19	
CD36A4-BK	CD36A4-GY		2	15.0	.59	1.089.3603.19	
CD36AP-BK	CD36AP-GY		Solid Insert		1.089.3699.19		
CD42A1-BK	CD42A1-GY	PG 42	3	14.0	.55	1.089.4203.19	
CD42AP-BK	CD42AP-GY		Solid Insert		1.089.4299.19		
CD48A1-BK	CD48A1-GY	PG 48	8	10.0	.39	1.089.4800.19	
CD48A2-BK	CD48A2-GY		6	12.0	.47	1.089.4801.19	
CD48A3-BK	CD48A3-GY		3	18.0	.71	1.089.4802.19	
CD48AP-BK	CD48AP-GY		Solid Insert		1.089.4899.19		

RJ45 Solution

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)		Part Numbers of Inserts Only
-40°F to 212°F (-40°C to 100°C)			Cable Diameter		
Black	Gray	See page 56 for thread specs	mm	Inches	
CD16AK-BK	CD16AK-GY		PG 16	5.7	
CD16AJ-BK	CD16AJ-GY	6.9		.27	1.089.16C-07

*Note: UL f1 (746C) rating applies to Black Nylon Fittings only.
*Note: This Insert has slotted holes.

*Note: RJ45 Solution has no approval ratings. NPT available on page 11. Metric available on page 12. Reference Diagram on page 12.

Dome Fittings also available with the following approvals:



www.SealconEX.com

Fittings with Multi-Hole Inserts are also available with a Flex Nut.

To order, substitute "CF" for "CD"
(e.g. CD09A1-BK becomes CF09A1-BK)

"BP" (Billet Plugs) available upon request.



For Strain Relief Specifications and Dimensions refer to page 24.