













	Locking Nuts - Page 29 · Black & Gray Nylon · Nickel Plated Brass	
	O-Rings - Page 31 · Buna-N · Silicone · FKM	
	Hole Plug - Page 32-34 Dome Plugs: · Buna-N · FKM Hex Plugs: · Black Nylon · Nickel Plated Brass · Stainless Steel	
	Wrenches - Page 34 · Deep Socket Wrenches	
	Thread Reducers - Page 37-39 Reduces a Type of (NPT, PG, Metric) · Gray Nylon · Black Nylon · FKM · Stainless Steel	
	Page 30 - Locking Nuts EMI/RFI Proof (Nickel Plated Brass) · Zinc Plated Steel · Stainless Steel (303) - INOX	
	Page 31 - Seal Rings Polyethylene · Fiber-Reinforced Plastic	
	Page 32-33 - Blind Plug/Clamp Blind Plugs: · Black Nylon Cable Clamp: Nickel Plated Brass	
	Page 35-36 - Thread Adapters Converts a Type of (NPT, PG, Metric) Threads · Black Nylon · Nickel Plated Brass	
	Page 40 - Thread Enlargers Enlarges a Type of (NPT, PG, Metric) Threads · Black Nylon · Nickel Plated Brass	

Accessories - Locking Nuts Nylon & Nickel Plated Brass - PG / NPT / Metric Threads

Nylon: Black & Gray Locking Nuts*				
Part Numbers		Thread Type & Size	Dimens. Inches (mm)	
-40°F to 212°F (-40°C to 100°C)			G	F
		See page 56 for thread specs	Thickness	Wrench Flats
NP-07-BK	NP-07-GY		PG 7	.20 (5)
NP-09-BK	NP-09-GY	PG 9	.20 (5)	.87 (22)
NP-11-BK	NP-11-GY	PG 11	.20 (5)	.94 (24)
NP-13-BK	NP-13-GY	PG 13 / 13.5	.24 (6)	1.06 (27)
NP-16-BK	NP-16-GY	PG 16	.24 (6)	1.18 (30)
NP-21-BK	NP-21-GY	PG 21	.28 (7)	1.41 (36)
NP-29-BK	NP-29-GY	PG 29	.28 (7)	1.81 (46)
NP-36-BK	NP-36-GY	PG 36	.31 (8)	2.36 (60)
NP-42-BK	NP-42-GY	PG 42	.31 (8)	2.56 (65)
NP-48-BK	NP-48-GY	PG 48	.31 (8)	2.76 (70)
<hr/>				
NN-09-BK	NN-09-GY	3/8" NPT	.28 (7)	.94 (24)
NN-13-BK	NN-13-GY	1/2" NPT	.24 (6)	1.06 (27)
NN-21-BK	NN-21-GY	3/4" NPT	.28 (7)	1.26 (32)
NN-29-BK	NN-29-GY	1" NPT	.28 (7)	1.57 (40)
<hr/>				
NM-12-BK	NM-12-GY	M12 X 1.5	19 (4.79)	.86 (22)
NM-16-BK	NM-16-GY	M16 X 1.5	.20 (5)	.87 (22)
NM-20-BK	NM-20-GY	M20 X 1.5	.24 (6)	1.06 (27)
NM-25-BK	NM-25-GY	M25 X 1.5	.26 (6.5)	1.26 (32)
NM-32-BK	NM-32-GY	M32 X 1.5	.28 (7)	1.61 (41)
NM-40-BK	NM-40-GY	M40 X 1.5	.28 (7)	1.97 (50)
NM-50-BK	NM-50-GY	M50 X 1.5	.31 (8)	2.36 (60)
NM-63-BK	NM-63-GY	M63 X 1.5	.31 (8)	2.95 (75)

* V0 Rated



Nickel Plated Brass: Locking Nuts				
Part Numbers		Thread Type & Size	Dimens. Inches (mm)	
Nickel Plated Brass			G	F
		See page 56 for thread specs	Thickness	Wrench Flats
NP-07-BR			PG 7	.11 (2.8)
NP-09-BR		PG 9	.11 (2.8)	.71 (18)
NP-11-BR		PG 11	.12 (3)	.83 (21)
NP-13-BR		PG 13 / 13.5	.12 (3)	.91 (23)
NP-16-BR		PG 16	.12 (3)	1.02 (26)
NP-21-BR		PG 21	.14 (3.5)	1.26 (32)
NP-29-BR		PG 29	.16 (4)	1.61 (41)
NP-36-BR		PG 36	.20 (5)	2.01 (51)
NP-42-BR		PG 42	.20 (5)	2.36 (60)
NP-48-BR		PG 48	.22 (5.5)	2.52 (64)
<hr/>				
NN-09-BR		3/8" NPT	.19 (4.79)	.82 (22)
NN-13-BR		1/2" NPT	.12 (3)	.94 (24)
NN-21-BR		3/4" NPT	.14 (3.5)	1.18 (30)
NN-29-BR		1" NPT	.14 (3.5)	1.38 (35)
<hr/>				
NM-06-BR		M6 X 1.0	.10 (2.5)	.39 (10)
NM-08-BR		M8X1.25	.10 (2.5)	.51 (13)
NM-10-BR		M10 X 1.5	.11 (2.8)	.51 (13)
NM-12-BR		M12 X 1.5	.11 (2.8)	.59 (15)
NM-16-BR		M16 X 1.5	.11 (2.8)	.75 (19)
NM-20-BR		M20 X 1.5	.12 (3)	.91 (23)
NM-25-BR		M25 X 1.5	.14 (3.5)	1.14 (29)
NM-32-BR		M32 X 1.5	.16 (4)	1.42 (36)
NM-40-BR		M40 X 1.5	.18 (4.5)	1.77 (45)
NM-50-BR		M50 X 1.5	.22 (5.5)	2.17 (55)
NM-63-BR		M63 X 1.5	.24 (6)	2.76 (70)

* German Lloyd only applies to Nickel Plated Brass Locking Nuts.

Additional: Nickel Plated Brass Extra Small & Large Locking Nuts are available in Metric: (M6, M8, M10, M63, M75, M80, M90, M100, M110). See Page 15.

For Material Specifications and Approval Information refer to page 52.