


The Metal Series range of protective cable conduits are particularly resistant to mechanical stresses. The conduit pipes made of galvanized steel are able to withstand high pressure loads. Matching metal fittings complete the range, ensuring, that the system is 100% industrial grade.



Fit
RoHS

Suggested Clearance Hole for Non-Threaded Mounting


Galvanized Steel: - IP 40

Part Numbers -148°F to 572°F (-100°C to 300°C)	DN Size	Dimensions in Inches (mm)			
		d Inner Diameter	D Outer Diameter	Roll Length (Ft.)	R mm
GS-0811-SA	7	.30 (7.5)	.41 (10.5)	164	25
GS-0912-SA	9	.35 (9)	.47 (12)	164	30
GS-1114-SA	11	.43 (11)	.55 (14)	164	30
GS-1417-SA	14	.55 (14)	.67 (17)	164	40
GS-1619-SA	16	.63 (16)	.75 (19)	164	45
GS-2124-SA	21	.83 (21)	.94 (24)	164	55
GS-2630-SA	26	1.02 (26)	1.18 (30)	82	55
GS-3741-SA	37	1.46 (37)	1.61 (41)	82	80
GS-4044-SA	40	1.57 (40)	1.73 (44)	82	80
GS-5155-SA	51	2.01 (51)	2.17 (55)	82	90



Extreme Temperatures

Suggested Clearance Hole for Non-Threaded Mounting



Fit S
RoHS

Galvanized Steel w/ PVC Coating : - IP 65

Part Numbers -5°F to 158°F (-15°C to 70°C)	DN Size	Dimensions in Inches (mm)			
		d Inner Diameter	D Outer Diameter	Roll Length (Ft.)	R mm
GS-0812-SB	7	.30 (7.5)	.45 (11.5)	164	25
GS-0913-SB	9	.35 (9)	.51 (13)	164	30
GS-1115-SB	11	.43 (11)	.59 (15)	164	30
GS-1418-SB	14	.55 (14)	.71 (18)	164	40
GS-1620-SB	16	.63 (16)	.79 (20)	164	45
GS-2125-SB	21	.83 (21)	.98 (25)	164	55
GS-2631-SB	26	1.02 (26)	1.22 (31)	82	55
GS-3742-SB	37	1.46 (37)	1.65 (42)	82	80
GS-4045-SB	40	1.57 (40)	1.77 (45)	82	80
GS-5156-SB	51	2.01 (51)	2.20 (56)	82	90



Metal Fit Fitting: Nickel Plated Brass - IP 54

Part Numbers -4°F to 176°F (-20°C to 80°C)	Thread Type & Size See page 56 for thread specs	Fits Conduit DN Size	Dimensions in Inches (mm)				
			A Clearance Hole +.01" (+.25 mm)	d Inner Diameter	TL Thread Length	L Body Length	F Wrench Flat
MFM1207-BR	M12 X 1.5	7	.47 (12)	.24 (6)	.31 (8)	.94 (24)	.59 (15)
MFM1609-BR	M16 X 1.5	9	.63 (16)	.28 (7)	.31 (8)	.94 (24)	.79 (20)
MFM1611-BR	M16 X 1.5	11	.63 (16)	.35 (9)	.39 (10)	1.02 (26)	.79 (20)
MFM2014-BR	M20 X 1.5	14	.79 (20)	.47 (12)	.39 (10)	1.02 (26)	.87 (22)
MFM2016-BR	M20 X 1.5	16	.79 (20)	.55 (14)	.39 (10)	1.02 (26)	.87 (22)
MFM2521-BR	M25 X 1.5	21	.98 (25)	.71 (18)	.39 (10)	1.06 (27)	1.10 (28)
MFM3226-BR	M32 X 1.5	26	1.26 (32)	.91 (23)	.47 (12)	1.22 (31)	1.38 (35)
MFM4037-BR	M40 X 1.5	37	1.57 (40)	1.32 (33.5)	.55 (14)	1.42 (36)	1.77 (45)
MFM5040-BR	M50 X 1.5	40	1.97 (50)	1.46 (37)	.55 (14)	1.42 (36)	2.17 (55)
MFM6351-BR	M63 X 1.5	51	2.48 (63)	1.81 (46)	.55 (14)	1.42 (36)	2.56 (65)
MFN1407-BR	NPT 1/4"	7	.49 (12.5)	.24 (6)	.39 (10)	1.02 (26)	.59 (15)
MFN3809-BR	NPT 3/8"	9	.68 (17.2)	.28 (7)	.45 (11.5)	1.08 (27.5)	.79 (20)
MFN3811-BR	NPT 3/8"	11	.68 (17.2)	.35 (9)	.45 (11.5)	1.08 (27.5)	.79 (20)
MFN1214-BR	NPT 1/2"	14	.83 (21.1)	.47 (12)	.51 (13)	1.14 (29)	.87 (22)
MFN1216-BR	NPT 1/2"	16	.83 (21.1)	.55 (14)	.51 (13)	1.14 (29)	.87 (22)
MFN3421-BR	NPT 3/4"	21	1.05 (26.7)	.71 (18)	.59 (15)	1.25 (32)	1.10 (28)
MFN1026-BR	NPT 1"	26	1.35 (34.3)	.91 (23)	.59 (15)	1.34 (34)	1.38 (35)
MFN5437-BR	NPT 1-1/4"	37	1.7 (43.2)	1.32 (33.5)	.63 (16)	1.50 (38)	1.77 (45)
MFN6440-BR	NPT 1-1/2"	40	1.9 (48.3)	1.46 (37)	.71 (18)	1.57 (40)	2.17 (55)
MFN2051-BR	NPT 2"	51	2.4 (61)	1.81 (46)	.79 (20)	1.65 (42)	2.56 (65)

Metal Fit S Fitting (Swivel): Nickel Plated Brass - IP 54

Part Numbers -4°F to 176°F (-20°C to 80°C)	Thread Type & Size See page 56 for thread specs	Fits Conduit DN Size	Dimensions in Inches (mm)				
			A Clearance Hole +.01" (+.25 mm)	d Inner Diameter	TL Thread Length	L Body Length	F Wrench Flat
MFSM1207-BR	M12 X 1.5	7	.47 (12)	.24 (6)	.31 (8)	1.06 (27)	.59 (15)
MFSM1609-BR	M16 X 1.5	9	.63 (16)	.28 (7)	.31 (8)	1.06 (27)	.79 (20)
MFSM1611-BR	M16 X 1.5	11	.63 (16)	.35 (9)	.39 (10)	1.14 (29)	.79 (20)
MFSM2014-BR	M20 X 1.5	14	.79 (20)	.47 (12)	.39 (10)	1.14 (29)	.87 (22)
MFSM2016-BR	M20 X 1.5	16	.79 (20)	.55 (14)	.39 (10)	1.14 (29)	.87 (22)
MFSM2521-BR	M25 X 1.5	21	.98 (25)	.71 (18)	.39 (10)	1.22 (31)	1.10 (28)
MFSM3226-BR	M32 X 1.5	26	1.26 (32)	.91 (23)	.47 (12)	1.38 (35)	1.38 (35)
MFSM4037-BR	M40 X 1.5	37	1.57 (40)	1.32 (33.5)	.55 (14)	1.61 (41)	1.77 (45)
MFSM5040-BR	M50 X 1.5	40	1.97 (50)	1.46 (37)	.55 (14)	1.61 (41)	2.17 (55)
MFSM6351-BR	M63 X 1.5	51	2.48 (63)	1.81 (46)	.55 (14)	1.61 (41)	2.56 (65)
MFSN1407-BR	NPT 1/4"	7	.49 (12.5)	.24 (6)	.39 (10)	1.14 (29)	.59 (15)
MFSN3809-BR	NPT 3/8"	9	.68 (17.2)	.28 (7)	.45 (11.5)	1.20 (30.5)	.79 (20)
MFSN3811-BR	NPT 3/8"	11	.68 (17.2)	.35 (9)	.45 (11.5)	1.20 (30.5)	.79 (20)
MFSN1214-BR	NPT 1/2"	14	.83 (21.1)	.47 (12)	.51 (13)	1.25 (32)	.87 (22)
MFSN1216-BR	NPT 1/2"	16	.83 (21.1)	.55 (14)	.51 (13)	1.14 (32)	.87 (22)
MFSN3421-BR	NPT 3/4"	21	1.05 (26.7)	.71 (18)	.59 (15)	1.42 (36)	1.10 (28)
MFSN1026-BR	NPT 1"	26	1.35 (34.3)	.91 (23)	.59 (15)	1.54 (39)	1.38 (35)
MFSN5437-BR	NPT 1-1/4"	37	1.7 (43.2)	1.32 (33.5)	.63 (16)	1.69 (43)	1.77 (45)
MFSN6440-BR	NPT 1-1/2"	40	1.9 (48.3)	1.46 (37)	.71 (18)	1.77 (45)	2.17 (55)
MFSN2051-BR	NPT 2"	51	2.4 (61)	1.81 (46)	.79 (20)	1.85 (47)	2.56 (65)