



Metal Fit Pro: Nickel Plated Brass - IP 67

Part Numbers -4°F to 176°F (-20°C to 80°C)	Thread Type & Size	Fits Conduit DN Size A / B / C	Dimensions in Inches (mm)						
			A	d	D	TL	L	F ₁	F
			Clearance Hole +.01" (+.25 mm)	Inner Diameter	Outer Diameter	Thread Length	Body Length	Wrench Flat	Wrench Flat
MPM1209-BR	M12 X 1.5	- / 9 / 9	.47 (12)	.65 (16.5)	.96 (24.5)	.39 (10)	1.22 (31)	.79 (20)	.87 (22)
MPM1611-BR	M16 X 1.5	10 / 11 / 11	.63 (16)	.75 (19)	1.15 (29.2)	.39 (10)	1.38 (35)	.94 (24)	1.02 (26)
MPM1612-BR	M16 X 1.5	12 / 13 / 13	.63 (16)	.87 (22)	1.28 (32.6)	.45 (11.5)	1.54 (39)	1.06 (27)	1.14 (29)
MPM2016-BR	M20 X 1.5	16 / 16 / 16	.79 (20)	.87 (22)	1.28 (32.6)	.51 (13)	1.52 (38.7)	1.06 (27)	1.14 (29)
MPM2521-BR	M25 X 1.5	21 / 21 / 21	.98 (25)	1.08 (27.5)	1.53 (38.8)	.59 (15)	1.61 (41)	1.30 (33)	1.38 (35)
MPM3226-BR	M32 X 1.5	27 / 26 / 26	1.26 (32)	1.36 (34.5)	1.97 (50)	.59 (15)	1.93 (49)	1.70 (43)	1.77 (45)
MPM4035-BR	M40 X 1.5	35 / 35 / 35	1.57 (40)	1.71 (43.5)	2.36 (60)	.63 (16)	2.01 (51)	2.05 (52)	2.13 (54)
MPM5040-BR	M50 X 1.5	40 / 40 / 40	1.97 (50)	1.95 (49.5)	2.73 (69.3)	.71 (18)	2.40 (61)	2.36 (60)	2.48 (63)
MPM6351-BR	M63 X 1.5	51 / 51 / 51	2.48 (63)	2.44 (62)	3.35 (85)	.79 (20)	2.87 (73)	2.91 (74)	3.03 (77)
MPN1410-BR	1/4" NPT	10 / 11 / 11	.49 (12.5)	.65 (16.5)	.96 (24.5)	.39 (10)	1.22 (31)	.79 (20)	.87 (22)
MPN3812-BR	3/8" NPT	12 / 13 / 13	.68 (17.2)	.75 (19)	1.15 (29.2)	.45 (11.5)	1.38 (35)	.79 (20)	.87 (22)
MPN1216-BR	1/2" NPT	16 / 16 / 16	.83 (21.1)	.87 (22)	1.28 (32.6)	.51 (13)	1.52 (38.7)	1.06 (27)	1.14 (29)
MPN3421-BR	3/4" NPT	21 / 21 / 21	1.05 (26.7)	1.08 (27.5)	1.53 (38.8)	.59 (15)	1.61 (41)	1.30 (33)	1.38 (35)
MPN1026-BR	1" NPT	27 / 26 / 26	1.35 (34.3)	1.36 (34.5)	1.97 (50)	.59 (15)	1.93 (49)	1.70 (43)	1.77 (45)
MPN5435-BR	1-1/4" NPT	35 / 35 / 35	1.7 (43.2)	1.71 (43.5)	2.36 (60)	.63 (16)	2.01 (51)	2.05 (52)	2.13 (54)
MPN6440-BR	1-1/2" NPT	40 / 40 / 40	1.9 (48.3)	1.95 (49.5)	2.73 (69.3)	.71 (18)	2.40 (61)	2.36 (60)	2.48 (63)
MPN2051-BR	2" NPT	51 / 51 / 51	2.4 (61)	2.44 (62)	3.35 (85)	.79 (20)	2.87 (73)	2.91 (74)	3.03 (77)

RoHS Fit Pro





Metal Pro Series offers a safe protection against heat and cold, intense mechanical loads and abrasion. The conduits pipes are designed as multi-layer variants. They are available with PVC-Coating or exterior metal braiding. Fittings of the Metal Fit Pro Series provides perfect matching for all Metal Pro conduits.



Metal Fit Pro S (Swivel): Nickel Plated Brass - IP 67

Part Numbers -4°F to 176°F (-20°C to 80°C)	Thread Type & Size	Fits Conduit DN Size A / B / C	Dimensions in Inches (mm)						
			A	d	D	TL	L	F ₁	F
			Clearance Hole +.01" (+.25 mm)	Inner Diameter	Outer Diameter	Thread Length	Body Length	Wrench Flat	Wrench Flat
MPSM1209-BR	M12 X 1.5	- / 9 / 9	.47 (12)	.65 (16.5)	.96 (24.5)	.39 (10)	1.34 (34)	.79 (20)	.87 (22)
MPSM1611-BR	M16 X 1.5	10 / 11 / 11	.63 (16)	.75 (19)	1.15 (29.2)	.39 (10)	1.38 (35)	.79 (20)	.87 (22)
MPSM1612-BR	M16 X 1.5	12 / 13 / 13	.63 (16)	.87 (22)	1.28 (32.6)	.45 (11.5)	1.46 (37)	.94 (24)	1.02 (26)
MPSM2016-BR	M20 X 1.5	16 / 16 / 16	.79 (20)	.87 (22)	1.28 (32.6)	.51 (13)	1.61 (41)	1.06 (27)	1.14 (29)
MPSM2521-BR	M25 X 1.5	21 / 21 / 21	.98 (25)	1.08 (27.5)	1.53 (38.8)	.59 (15)	1.73 (44)	1.30 (33)	1.38 (35)
MPSM3226-BR	M32 X 1.5	27 / 26 / 26	1.26 (32)	1.36 (34.5)	1.97 (50)	.59 (15)	2.01 (51)	1.70 (43)	1.77 (45)
MPSM4035-BR	M40 X 1.5	35 / 35 / 35	1.57 (40)	1.71 (43.5)	2.36 (60)	.63 (16)	2.13 (54)	2.06 (52)	2.13 (54)
MPSM5040-BR	M50 X 1.5	40 / 40 / 40	1.97 (50)	1.95 (49.5)	2.73 (69.3)	.71 (18)	2.52 (64)	2.36 (60)	2.48 (63)
MPSM6351-BR	M63 X 1.5	51 / 51 / 51	2.48 (63)	2.44 (62)	3.35 (85)	.79 (20)	2.99 (76)	2.91 (74)	3.03 (77)
MPSN1410-BR	1/4" NPT	10 / 11 / 11	.49 (12.5)	.65 (16.5)	.96 (24.5)	.39 (10)	1.38 (35)	.79 (20)	.87 (22)
MPSN3812-BR	3/8" NPT	12 / 13 / 13	.68 (17.2)	.75 (19)	1.15 (29.2)	.45 (11.5)	1.46 (37)	.79 (20)	.87 (22)
MPSN1216-BR	1/2" NPT	16 / 16 / 16	.83 (21.1)	.87 (22)	1.28 (32.6)	.51 (13)	1.61 (41)	1.06 (27)	1.14 (29)
MPSN3421-BR	3/4" NPT	21 / 21 / 21	1.05 (26.7)	1.08 (27.5)	1.53 (38.8)	.59 (15)	1.73 (44)	1.30 (33)	1.38 (35)
MPSN1026-BR	1" NPT	27 / 26 / 26	1.35 (34.3)	1.36 (34.5)	1.97 (50)	.59 (15)	2.01 (51)	1.70 (43)	1.77 (45)
MPSN5435-BR	1-1/4" NPT	35 / 35 / 35	1.7 (43.2)	1.71 (43.5)	2.36 (60)	.63 (16)	2.13 (54)	2.05 (52)	2.13 (54)
MPSN6440-BR	1-1/2" NPT	40 / 40 / 40	1.9 (48.3)	1.95 (49.5)	2.73 (69.3)	.71 (18)	2.52 (64)	2.36 (60)	2.48 (63)
MPSN2051-BR	2" NPT	51 / 51 / 51	2.4 (61)	2.44 (62)	3.35 (85)	.79 (20)	2.99 (76)	2.91 (74)	3.03 (77)

RoHS Fit Pro S



RoHS

Metal Fit Clip: Metal

Part Numbers	Fits to Metal Series	Fits to Metal Pro A	Fits to Metal Pro B,C	Size DN
MFC07	7	-	-	7
MFC09	9	-	-	9
MFC11	11	-	-	11
MFC14	11	-	-	14
MFC16	16	16	16	16
MFC21	21	21	21	21
MFC27	-	27	26	26/27
MFC35	35	35	35	35
MFC51	51	-	-	51



Optional Locking Nuts,
O-Rings & Other
Accessories starting
on Page 29 - 40.