

PRODUCT SPOTLIGHT

UL Fiberglass Wall Cabinet

Sizes:

11.8" x 9.8" x 5.5" through 31.5" x 23.6" x 11.8" in
300 x 250 x 140 through 800 x 600 x 300mm



Fiberglass Wall Cabinet in Brief:

- Available with plain sides or with a polycarbonate window
- Superb temperature resistance
- Sturdy construction and high resistance to corrosion and solvents
- Suitable for highly demanding environments such as waste water treatment and the petrochemical/chemical industries
- Quick fixture brackets at the back allow fitting without drilling
- Built-in protective edge allows you to open the door 180° in installations and also prevents entry of water when opening the door
- Vertical patterns on the inner side of the door enables correct fitting of devices

Contents of the Product Package:

- Enclosure base
- Door
- Lock with 1/4 turn latch

Conformity	
GRP enclosures:	CE RoHS UL cUL GL
Technical information	
UL File no:	E189312
UL category:	NITW, NITW7
Environmental type (UL):	4, 4x, 12
Operating temperature:	-40 °F... 176 °F (-40 °C... +80 °C)
Short term temperature range:	-58 °F... 284 °F (-50 °C... +140 °C)
Flammability rating:	UL 746C
Degree of protection:	IP66
Impact resistance:	IK10, models with window IK07
Insulation:	Class II
Material	
Base/cover:	Fiberglass reinforced Polycarbonate
Lock:	Double bit DIN 0.12 inch (3.0 mm)
Gasket:	PUR (polyurethane)
Enclosure side types	
GRP enclosures:	Plain sides
Standard color	
Base/cover:	Gray RAL 7035