M12 POWER CONNECTOR

M20 x 1.5

M20 x 1.5 .79" (20.2 + 0.1 mm)

HOUSINGS, ACCESSORIES

/12 Power Panel Co	nnector, Male Thread, Single Hole, Orientable	Туре	Coding	Part Number
	M12 × 1	Front Mounting, Single Hole		
		Thread M16K, L (Crimp)SA712-7.K42.200.000		
		Thread M20S, T (Screw)SA712-7.S42.200.000		
			G SHOWS CODING S + T	-

M12 Power Pane	el Connector, Female Thread, Single Hole, Orientable	Туре	Coding	Part Number
		Front Mounting, Single Hole		
	¥.90" (23 mm) ¥.90" (23 mm) 40 × 1.5 M20 × 1.5 .79" (20.2 + 0.1 mm)	Thread M16	K, L (Crimp)	.SA712-7.K44.200.000
		Thread M20	S, T (Screw)	.SA712-7.S44.200.000
			IG SHOWS CODING S + T	

*MOLDED CORDSETS ALSO AVAILABLE - CONTACT SEALCON FOR DETAILS

S+T CODINGS REQUIRE FERRULES FOR INSTALLATION, SEE PAGE 13 FOR SPECIFICATIONS





Plastic Protective Cap for connectors with Male thread......SA712-7.000.980.161 with Female thread.....SA712-7.000.980.162





Brass Protective Cap for connectors with Male thread SA712-7.010.900.162



Tool Adapter for tightening or loosening knurled nuts for M12 Power / M16 \$7.010.900.191



PIN INSERTS MOUNTABLE WITH MALE THREAD HOUSINGS ONLY. SOCKET INSERTS MOUNTABLE WITH FEMALE THREAD HOUSINGS ONLY.

Brass Protective Cap with chain for connectors

with Female thread



Length 70 mm...... SA712-7.010.9S0.705



Crimp Tool for manual crimping of machined crimp contacts for signal connectors M12, M16 and M23......S7.000.900.908



Screw Tool, adjustable 0.5 - 1.7 Nm S7.010.900.190



www.SealconUSA.com | (303) 699-1135 | (800) 456-9012 Dimensions & Specifications are subject to change without prior notice