

GENESIS SERIES G

SIZE: 20x16x8 TO 24x24x10 INCHES







Features and Benefits

- Unique Multi-Max Rail Mounting System®
- Sturdy, full length piano hinged door
- Made of rugged industrial polycarbonate material
- Extra rigid construction with unique internal Multi-Max frame
- Available in four non-metallic latch or three-point latch configurations

Available Accessories

- Multi-Max Rails®
- Door Stop Kit
- Back and Swing Panels
- Panel Pads
- Self-Tapping Screws
- Fan Shroud Kits
- Pole Mounting Kits
- Swing Out Panel System
- 3-Point Latching System
- Multi-Max Frame



Conformity	
Certificates and Approvals:      	
Technical information	
UL File no:	E207562
Environmental Type (UL):	4X, 6P
Instrumented Dart Impact:	565 in/lb. @ 73 °F
Falling Ball Impact:	900 in/lb. (UL-746@ 73 °F)
Deflection Temperature:	270 °F (ASTM D648 @ 264 PSI)
Modulus of Elasticity:	340 KSI (ASTM D790)
Temperature Range:	-40 °F to 265 °F (-40 °C to 129 °C)
UL Flame Rating:	5VA (UL 94)
Outdoor UV Exposure:	F1 (UL)

Genesis Series G Polycarbonate Enclosures

Part Number	Length Inch (mm)	Width Inch (mm)	Depth Inch (mm)	IP 66	IP 68	Hinged Cover	Opaque Cover	Clear Cover	Mounting Flange	Multi-Max Rail System	3-Point Latch	1/4 Turn Latch	Non-Metal Locking Latch
SG201608	20 (508)	16 (406.4)	8 (203.2)	•	•	•	•		•	•			•
SG201608C	20 (508)	16 (406.4)	8 (203.2)	•	•	•		•	•	•			•
SG201608TPL	20 (508)	16 (406.4)	8 (203.2)	•		•	•		•	•	•		
SG201608CTPL	20 (508)	16 (406.4)	8 (203.2)	•		•		•	•	•	•		
SG201608QTL	20 (508)	16 (406.4)	8 (203.2)	•		•	•		•	•		•	
SG201608CQTL	20 (508)	16 (406.4)	8 (203.2)	•		•		•	•	•		•	
SG201608E	20 (508)	16 (406.4)	8 (203.2)	•	•	•	•		•				•
SG201608CE	20 (508)	16 (406.4)	8 (203.2)	•	•	•		•	•				•
SG242410	24 (609.6)	24 (609.6)	10 (254)	•	•	•	•		•	•			•
SG242410C	24 (609.6)	24 (609.6)	10 (254)	•	•	•		•	•	•			•
SG242410TPL	24 (609.6)	24 (609.6)	10 (254)	•		•	•		•	•	•		
SG242410CTPL	24 (609.6)	24 (609.6)	10 (254)	•		•		•	•	•	•		
SG242410QTL	24 (609.6)	24 (609.6)	10 (254)	•		•	•		•	•		•	
SG242410CQTL	24 (609.6)	24 (609.6)	10 (254)	•		•		•	•	•		•	
SG242410E	24 (609.6)	24 (609.6)	10 (254)	•	•	•	•		•				•
SG242410CE	24 (609.6)	24 (609.6)	10 (254)	•	•	•		•	•				•

NOTE: Sizes reflect Interior dimensions

SG201608 & SG242410 Include the following

Enclosure, Multi-Max Frame, Set of Four Multi-Max Rails® (with Screws), and either two or four Latches




Multi-Max Frame

+



Multi-Max Rail Mounting System®

+



Latches