





Conformity	
Certificates and Approvals:    	
Technical information	
UL File no:	E189312
UL category:	NITW, NITW7
Environmental type (UL):	4, 4X, 12
Outdoor suitability:	UL 746C (f1) rated material
Operating temperature:	-40°F... 176°F (-40°C ... +80°C)
Short term temperature range:	-58°F... 248°F (-50°C... +120°C)
Flammability rating:	UL 746C
Impact resistance:	IK10, models with window IK07
Insulation:	Class II

SERIES N - NOOKBOX

SIZE: 12x10x5 TO 31x24x12 INCHES

Features and Benefits

- Wall Mount Cabinet Style Enclosure
- Available with plain sides or with a polycarbonate window
- Fiberglass Reinforced Polyester with superb temperature resistance
- Available in 7 different size options
- Sturdy construction and high resistance to corrosion and solvents
- Suitable for highly demanding environments such as waste water treatment and the petrochemical/chemical industries
- Quick fixture brackets at the back allow fitting without drilling
- Built-in protective edge allows you to open the door 180° in installations and prevents entry of water when opening the door

Available Accessories

- Mounting Plates
- DIN Rails
- DIN Mounting Base
- Internal Doors
- Wall Mounting Feet
- T-Handle
- T-Handle with Key Lock
- Swing Handle
- Locks



Series N - NookBox Fiberglass Enclosures

Part Number	Length Inch (mm)	Width Inch (mm)	Depth Inch (mm)	IP 66	Opaque Cover	Window Cover	Hinged Cover	Plain Sides
S360253014PU	11.81 (300)	9.84 (250)	5.51 (140)	•	•		•	•
S360253014WU	11.81 (300)	9.84 (250)	5.51 (140)	•		•	•	•
S360304020PU	15.74 (400)	11.81 (300)	7.87 (200)	•	•		•	•
S360304020WU	15.74 (400)	11.81 (300)	7.87 (200)	•		•	•	•
S360404020PU	15.74 (400)	15.74 (400)	7.87 (200)	•	•		•	•
S360404020WU	15.74 (400)	15.74 (400)	7.87 (200)	•		•	•	•
S360405020PU	19.68 (500)	15.74 (400)	7.87 (200)	•	•		•	•
S360405020WU	19.68 (500)	15.74 (400)	7.87 (200)	•		•	•	•
S360406023PU	23.62 (600)	15.74 (400)	9.05 (230)	•	•		•	•
S360406023WU	23.62 (600)	15.74 (400)	9.05 (230)	•		•	•	•
S360506023PU	23.62 (600)	19.68 (500)	9.05 (230)	•	•		•	•
S360506023WU	23.62 (600)	19.68 (500)	9.05 (230)	•		•	•	•
S360608030PU	31.49 (800)	23.62 (600)	11.81 (300)	•	•		•	•
S360608030WU	31.49 (800)	23.62 (600)	11.81 (300)	•		•	•	•

NOTE: Sizes reflect Exterior dimensions

Accessories

A wide range of accessories are available to ensure our enclosures meet your unique requirements



Plastic Mounting Feet



Metal Mounting Feet



Padlock Latch



Key Lock with T-Handle