





Conformity	
Certificates and Approvals:	   
Technical information	
UL File no:	E189312
UL category:	NITW
Environmental type (UL):	4, 4X, 6, 12, 13
Outdoor suitability:	UL 746C (f1) rated material
Operating temperature:	-40°F... +176°F (-40°C... +80°C)
Short term temperature range:	-40°F... +248°F (-40°C... +120°C)
Flammability rating:	UL 746C
Impact resistance:	IK08 (-13°F... +95°F / -25°C... +35°C)
Insulation:	Class II

PUSHBUTTON ENCLOSURES

SIZE: 3x3x3 TO 8x5x3 INCHES

Features and Benefits

- Available factory-made 4-way:
 - 22.5 mm PB size holes
 - 30.5 mm PB size holes
- Made of rugged industrial polycarbonate material
- Contemporary design with faceted corners and cover plugs
- Includes fastening pods inside the cover

Available Accessories

- Mounting Plates
- DIN Rails
- Mounting Feet
- Mounting Screws
- Screw Sets
- Breather Valve



* Buttons not Included

Pushbutton Enclosures

Part Number	Length Inch (mm)	Width Inch (mm)	Depth Inch (mm)	IP 66	IP 67	Opaque Cover	1 Hole	2 Holes	3 Holes	4 Holes	22.5 mm Holes	30.5 mm holes
S350P1225	3.2 (81.28)	3.1 (78.74)	3.4 (86.36)	•	•	•	•				•	
S350P1305	3.2 (81.28)	3.1 (78.74)	3.4 (86.36)	•	•	•	•					•
S350P2225	4.7 (119.38)	3.1 (78.74)	3.4 (86.36)	•	•	•		•			•	
S350P2305	6.3 (160.02)	3.1 (78.74)	3.4 (86.36)	•	•	•		•				•
S350P3225	6.3 (160.02)	3.1 (78.74)	3.4 (86.36)	•	•	•			•		•	
S350P3305	7.9 (200.66)	4.7 (119.38)	3.4 (86.36)	•	•	•			•			•
S350P4225	7.9 (200.66)	4.7 (119.38)	3.4 (86.36)	•	•	•				•	•	
S350P4305	7.9 (200.66)	4.7 (119.38)	3.4 (86.36)	•	•	•				•		•

NOTE: Sizes reflect Exterior dimensions

Pushbuttons

Empty non-metallic polycarbonate pushbutton enclosure series. These enclosures have excellent resistance against UV and are proven to withstand arctic and changing climates.

