Conformity										
Polycarbonate Enclosures:										
Technical information										
Instrumented Dart Impact @ 73° F	Inch / Pound 565									
Falling Ball Impact @ 73° F	UL-746 Inch / Pound 900									
Deflection Temperature @ 264 psi	emperature @ 264 psi ASTM D648 Degrees F 270									
Modulus of Elasticity	rn ASTM D790 ksi 340									
Temperature Range	Degrees F -40 to 265									
Flame Rating - UL	UL 94 - 5VA									
Outdoor UV Exposure	por UV Exposure UL - f1									
UL/C-UL-50 listed	L/C-UL-50 listed (files # E229365, # E207562)									
Material										
Base:	Polycarbonate Enclosure									
Cover:	Polycarbonate Hinged Cover									
Cover Screws:	Fiberglass Reinforced Polyamide									
Enclosure side types										
Polycarbonate enclosures:										
Standard color										
Base:	Light Gray in Color With High Gloss Finish									
Cover:	Opaque or Clear									

Comes with feet or flanges. This size also available with low profile hinge. Expansion box not shown.

# CE ROHS ( CE) MADE IN THE USA

#### Sealcon 10 x 8 x 2 INCH Enclosure

S10082 P/N	4X IP66	6P IP68	Hinged Cover	Screw Cover	Opaque Cover	Clear Cover	Mounting Feet	Mounting Flange	Stainless Steel Locking Latch	Non-Metallic Locking Latch
SH10082S	~	~		~	~		~			
SH10082SC	~	~		~		~	~			
SH10082SF	~	~		~	~			~		
SH10082SCF	~	~		~		>		~		
SH10082H	~		~	~	~		~			
SH10082HC	~		~	~		~	~			
SH10082HF	~		~	~	~			~		
SH10082HCF	~		~	~		>		~		
SH10082HLL	~		~		~		~		~	
SH10082HCLL	~		~			>	~		<b>~</b>	
SH10082HFLL	~		~		~			~	<b>~</b>	
SH10082HCFLL	~		~			~		~	~	
SH10082HNL	~		~		~		~			~
SH10082HCNL	~		~			>	~			~
SH10082HFNL	~		~		~			~		~
SH10082HCFNL	~		~			>		~		~
SH10082H-6P	~	~	~	~	~		~			
SH10082HC-6P	~	~	~	~		~	~			
SH10082HF-6P	~	~	~	~	~			~		
SH10082HCF-6P	~	~	~	~		>		~		

TORQUE SPECIFICATIONS - Mounting Brackets - 1/4"-20 x 0.25 SS, countersunk Phillips drive screws (torque limit = 20 in-lbs.) | Covers / Doors - Torque for corner screws is 10 in-lbs.

## **POLYCARBONATE ENCLOSURE**

SIZE 10 X 8 X 2 INCH

### 10 x 8 x 2 Inch Enclosure in Brief:

- Made in the USA
- Standard color light gray with a gloss finish.
- Best material bases, opaque covers and clear covers are all made of high-impact, UV resistant polycarbonate.
- Easy ordering one part number includes base, lid, mounting feet or flanges and all lid fastening hardware (mounting panels sold separately).
- Flexible interior mounting features the unique adjustable depth "T-Rail" back panel mounting system (back panel and adjustable brackets sold separately).
- Features multiple bosses for easy installation of devices and DIN rails.
- UL-50 / c-UL Listed (files # E229365, # E207562)

Sealcon's enclosures are the most durable, non-metallic NEMA UL rated enclosures available. From the extremely versatile mounting options inside the enclosure to having the most off-the shelf accessories, "Made In the USA"






SH10082HCNL

www.SealconUSA.com | (303) 699-1135 | (800) 456-9012 Dimensions & Specifications may be changed without prior notice





Accessories for 10x8x24 Inch

Comes with feet or flanges



Back Panels SABP1082 -Aluminum panel SSBP1082 -

**SPVCBP1082** -

Steel panel

PVC panel



Air Vents SVENT-3 -Aluminum louvered SVENT-2 -Outdoor labyrinth



#### Aluminum Swing Out Panels SABP-108USP/

USOPK-Complete panel kit SABP-108USP -Aluminum swing out panels only SUSOPK -Hardware only



#### Steel Swing Out Panels

SSBP-108USP/USOPK -Complete panel kit SBP-108USP - Steel swing out panels only SUSOPK - Hardware only



#### **Back Panel Adjustment Kit**

SBPAKG - Gray, Set Screw SBPAKB - Black, Set Screw SUBPAKG - Gray, Thumb Screw SUBPAKB - Black Thumb Screw



Mounting Feet & Flange Kits SMFKG - Premium line feet SMFKSS - Stainless steel feet SMFLK8 - 8" Flange kit

Din Rail SDIN8 - 2 rails, 4 screws




Pole Mounting Kits SPMKG-28 - 2" pole

**SPMKG-38** - 3" pole **SPMKG-48** - 4" pole **SMKG-128** - 12" pole


www.SealconUSA.com | (303) 699-1135 | (800) 456-9012 Dimensions & Specifications may be changed without prior notice







With our readily accessible inventory, you can rest assured that your order will ship quickly and without delay--minimizing any downtime. Experience the Sealcon difference!



www.SealconUSA.com | (303) 699-1135 | (800) 456-9012 Dimensions & Specifications may be changed without prior notice

