


For cable trunking and conduit installation




- without terminals
- for cable trunking and conduit installation
- included cable entry: 7 DPS 02, sealing range Ø 10-13,5 mm
- colour: grey, RAL 7035


rated insulation voltage	U _i = 690 V a.c./d.c.
material	PS (Polystyrene)
degree of protection	IP 54
mounting width	117 mm
mounting height	97 mm
max. installation depth	33 mm
width	139 mm
height	119 mm
depth	49 mm
weight	0,257 kg
in accordance with	IEC 60670-22

Drawings


Dimension drawing




For cable trunking and conduit installation



Detail mass



Box walls



Operating and ambient conditions

Application area	Suitable for indoor installation and outdoor installation, protected against weather influences
Ambient temperature	Maximum value + 40 °C Minimum value - 25 °C
Fire protection in the event of internal faults	Demands placed on electrical devices from standards and laws Minimum requirements - Glow wire test in accordance with IEC 60695-2-11: - 650°C for boxes and cable glands - 850°C for parts of insulating material necessary to retain current carrying parts in position
Burning behaviour	Glow wire test IEC 60695-2-11: 750 °C UL Subject 94: V-2 flame-retardant self-extinguishing
Degree of protection against mechanical load	IK07 (2 Joule)

Toxic behaviour

halogen-free

silicone-free

"halogen-free" in accordance with the examination of the cables
and insulated wires - corrosiveness of fumes - as per IEC 60754-2