

Nickel Plated Brass Liquid Tight Strain Relief Fittings Multi-Hole - PG Threads



Nickel Plated Brass



Part Numbers		Thread Type & Size	Dimensions in Inches (mm)			
-40°F to 212°F (-40°C to 100°C)			No. of Holes	Diameter of Holes		Part Numbers of Inserts Only
Dome	Flex**	mm		Inches		
CD07AP-BR	CF07AP-BR	PG 7 / 1/4" NPT	Solid Insert		1.089.0799.19	
CD09A1-BR	CF09A1-BR	PG 9	4	1.4	.06	1.089.0900.19
CD09A2-BR	CF09A2-BR		2	3.0	.12	1.089.0901.19
CD09A3-BR	CF09A3-BR		5	1.6	.06	1.089.0902.19
CD09A4-BR	CF09A4-BR		2	1.7	.07	1.089.0903.19
CD09A5-BR	CF09A5-BR		10	1.4	.06	1.089.0904.19
CD09A6-BR	CF09A6-BR		6	1.4	.06	1.089.0905.19
CD09A7-BR	CF09A7-BR		3	1.7	.07	1.089.0906.19
CD09A8-BR	CF09A8-BR		4	1.7	.07	1.089.0907.19
CD09A9-BR	CF09A9-BR		4	2.3	.09	1.089.0908.19
CD09AP-BR	CF09AP-BR		Solid Insert		1.089.0999.19	
CD11A1-BR	CF11A1-BR	PG 11	2	3.0	.12	1.089.1100.19
CD11A2-BR	CF11A2-BR		3	3.0	.12	1.089.1101.19
CD11A3-BR	CF11A3-BR		2	4.0	.16	1.089.1102.19
CD11A4-BR	CF11A4-BR		3	1.5	.06	1.089.1103.19
CD11A5-BR	CF11A5-BR		4	2.8	.11	1.089.1104.19
CD11AP-BR	CF11AP-BR	Solid Insert		1.089.1199.19		
CD13A1-BR	CF13A1-BR	PG 13 / 13.5	3	2.0	.08	1.089.1300.19
CD13A2-BR	CF13A2-BR		6	3.0	.12	1.089.1301.19
CD13A3-BR	CF13A3-BR		3	4.0	.16	1.089.1302.19
CD13A4-BR	CF13A4-BR		2	5.0	.20	1.089.1303.19
CD13A5-BR	CF13A5-BR		3	3.0	.12	1.089.1304.19
CD13A6-BR	CF13A6-BR		2	5.2	.20	1.089.1305.19
CD13A7-BR	CF13A7-BR		2	3.8	.15	1.089.1306.19
CD13A8-BR	CF13A8-BR		2	4.2	.17	1.089.1307.19
CD13A9-BR	CF13A9-BR		2	2.5	.10	1.089.1308.19
CD13AP-BR	CF13AP-BR		Solid Insert		1.089.1399.19	
CD16A1-BR	CF16A1-BR	PG 16	3	3.0	.12	1.089.1600.19
CD16A2-BR	CF16A2-BR		3	4.0	.16	1.089.1601.19
CD16A3-BR	CF16A3-BR		4	4.0	.16	1.089.1602.19
CD16A4-BR	CF16A4-BR		5	4.0	.16	1.089.1603.19
CD16A5-BR	CF16A5-BR		6	4.0	.16	1.089.1604.19
CD16A6-BR	CF16A6-BR		2	6.0	.24	1.089.1605.19
CD16A7-BR	CF16A7-BR		3	5.6	.22	1.089.1606.19
CD16A8-BR	CF16A8-BR		6	3.0	.12	1.089.1607.19
CD16A9-BR	CF16A9-BR		*4	3.0	.12	*1.089.1610.19
CD16A0-BR	CF16A0-BR		6	3.8	.15	1.089.1909.19
CD16AP-BR	CF16AP-BR	Solid Insert		1.089.1699.19		

*Note: This insert has slotted holes.
 **Note: Flex Fittings are not a standard item, assembly required.
 *Note: CSA and CE Approvals only applies to Dome Fittings.

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)			
-40°F to 212°F (-40°C to 100°C)			No. of Holes	Diameter of Holes		Part Numbers of Inserts Only
Dome	Flex**	mm		Inches		
CD21A1-BR	CF21A1-BR	PG 21	4	6.0	.24	1.089.2100.19
CD21A2-BR	CF21A2-BR		3	7.0	.28	1.089.2101.19
CD21A3-BR	CF21A3-BR		2	8.0	.31	1.089.2102.19
CD21A4-BR	CF21A4-BR		4	5.0	.20	1.089.2103.19
CD21A5-BR	CF21A5-BR		1	8.0	.31	1.089.2104.19
CD21A6-BR	CF21A6-BR		4	5.2	.20	1.089.2105.19
CD21A7-BR	CF21A7-BR		3	5.2	.20	1.089.2106.19
CD21A8-BR	CF21A8-BR		4/1	5.2 / 3.7	.20 / .15	1.089.2107.19
CD21A9-BR	CF21A9-BR		2	7.4	.29	1.089.2108.19
CD21AP-BR	CF21AP-BR		Solid Insert		1.089.2199.19	
CD29A1-BR	-	PG 29	6	6.5	.26	1.089.2900.19
CD29A2-BR	-		4	9.0	.35	1.089.2901.19
CD29A3-BR	-		4	9.5	.37	1.089.2902.19
CD29A9-BR	-		2	11.0	.43	1.089.2908.19
CD29AP-BR	-	Solid Insert		1.089.2999.19		
CD36A1-BR	-	PG 36	5	9.0	.35	1.089.3600.19
CD36A2-BR	-		7	9.0	.35	1.089.3601.19
CD36A3-BR	-		6	8.0	.31	1.089.3602.19
CD36A4-BR	-		2	15.0	.59	1.089.3603.19
CD36AP-BR	-	Solid Insert		1.089.3699.19		
CD42A1-BR	-	PG 42	3	14.0	.55	1.089.4203.19
CD42AP-BR	-		Solid Insert		1.089.4299.19	
CD48A1-BR	-	PG 48	8	10.0	.39	1.089.4800.19
CD48A2-BR	-		6	12.0	.47	1.089.4801.19
CD48A3-BR	-		3	18.0	.71	1.089.4802.19
CD48AP-BR	-		Solid Insert		1.089.4899.19	

RJ45 Solution					
Part Numbers		Thread Type & Size	Dimensions in Inches (mm)		
-40°F to 212°F (-40°C to 100°C)			Cable Diameter		Part Numbers of Inserts Only
Dome	Flex**	mm	Inches		
CD16AK-BR	CF16AK-BR	PG 16	5.7	.23	1.089.16C-06
CD16AJ-BR	CF16AJ-BR		6.9	.27	1.089.16C-07

*Note: RJ45 Solution has no approval ratings. Reference Diagram on page 24. For Strain Relief Fitting specifications and dimensions refer to page 14. For Material Specifications and Approval Information refer to page 52.



Optional Locking Nuts, O-Rings & Other Accessories starting on Page 29 - 40.

Dome Fittings also available with the following approvals:



www.SealconEX.com

Solid Plug can be customized!
 Multi-Hole Inserts are available in Silicone and FKM upon request.
 "BP" (Billet Plugs) available.

