


VariaPro Temp

Metr.



| | |
|-----------------------|--|
| Material | Nickel plated brass |
| Seal / O-Ring | VMQ (Silikon) |
| Protection | IP 68 – 10 bar within the specified clamping range |
| Operating Temperature | -60 °C – 200 °C |

- // Suitable for absolute low temperature applications
- // Also ideal for high temperatures up to 200 °C



| AG | \varnothing mm | GL | H mm | mm Dome Nut | mm Body | Number |
|------------|---------------------|----|---------|--------------------|----------------|-----------|
| M 20 x 1,5 | 7,0–14,0 | 6 | 27 | 22 | 24 | VT22MR-BR |
| M 25 x 1,5 | 11,0–18,0 | 7 | 29 | 27 | 30 | VT25MR-BR |
| M 32 x 1,5 | 16,0–25,0 | 8 | 34 | 36 | 40 | VT32MR-BR |
| M 40 x 1,5 | 21,0–32,0 | 8 | 40 | 46 | 50 | VT40MR-BR |

VariaPro Temp



- // For applications under extreme conditions
- // Suitable for absolute low temperature applications
- // Also ideal for high temperatures up to 200 °C
- // Integrated EMC connection
- // Large clamping range due to reducing insert
- // Integrated anti-twist protection during cable installation