

SEALCON

Leading Provider of Cable Management Solutions

M12 Power Circular Connectors



Compact & Powerful

 RoHS

 Deca
BDE



Circular Connectors - M12 Power Compact & Powerful

M12 goes Power!

A major milestone in an age of miniaturization we present the "NEW" M12 Power Connector!

This circular connector opens the door to entirely new applications and capabilities! Its high power transmission, compact design and the large temperature range are extraordinary features. The electro-mechanical features of this compact power connector are convincing!

- Power transmission to 16 A and 630 V
- Protection IP 67 and IP 69K
- Cable diameter up to 11 mm (0.43")
- Temperature range to 125 degree Celsius
- EMI (EMC) Shielding in standard version
- K, L, S, T Coding (4 & 5 positions)
- Robust metal housing
- Compact designs
- Optional stainless steel



Pending



Same performance
...more compact!



Circular Connectors - M12 Power Technical Data

Materials and Technical Data	
Housing	Copper-Zinc alloy / Die Cast INOX AISI 316 L TPU (Molded versions)
Housing surface	Nickel plated Black chrome-plated
Inserts (for contacts)	PBT Fire protection class V-0
Contacts	Copper alloy
Contact surface at point of contact	Gold plated
Minimum mating cycles	> 100
Seals / O-Rings	FKM / NBR
Temperature range	-40°C – 125°C (-40°F – 257°F)
Type of contacts	Crimp, screw
Protection	IP 67 / IP 69K
Cable diameter range	3 – 11 mm (.08 – .43")

Electrical Data				
Coding	S (Screw)	T (Screw)	K (Crimp)	L (Crimp)
Colors	black	dark grey	blue	grey
Number of positions	4 (3 + PE)	4	5 (4 + PE)	5 (4 + PE)
(mm ²) AWG	(0,5 – 1,5) AWG 20 – 16	(0,5 – 1,5) AWG 20 – 16	(0,75 – 2,5) AWG 18 – 14	(0,75 – 2,5) AWG 18 – 14
Nominal current [A]	12	12	16	16
Nominal voltage [V~] degree of protection 3	630	63	630	63
Test voltage (Breakdown voltage) [V~]	6000	1500	6000	1500
Insulation resistance [MΩ]	> 10 ⁶	> 10 ⁶	> 10 ⁶	> 10 ⁶
Max. contact resistance [mΩ]	< 3	< 3	< 3	< 3

Technical Information


Nominal Current: Allowable current (Amp), that can be transmitted by each contact continuously and simultaneously.

Nominal Voltage: Allowable voltage (Volt), that can be applied to each contact continuously and simultaneously.

Test Voltage: Voltage which, under certain conditions, a connector can be exposed to without breakdown.

Degree of Protection: Potential dirt accumulation of a disconnected connector in a certain environment.

Don't connect or disconnect HUMMEL Connectors under load.





Circular Connectors - M12 Power Overview


Straight & Elbow Connectors - Female/Male Threads

Page 6




Panel Mount Connectors - Female/Male Threads

Page 6




Molded Cordsets - Straight & Elbow - Female/Male Threads

Page 7



Inserts Configurations

Page 8




Contacts - Pins & Sockets

Page 8



Accessories

Page 7



Technical Data

Page 3

Benefits

Page 5

Assembly Instructions

Page 10

Limited Liability

Products, design, colors and dimensions are subject to change without prior notice. We reserve the right to make technical improvements on all our products, currently ordered or for future orders. It is the user's responsibility to verify all dimensions and technical data. HUMMEL AG and Sealcon LLC will assume no liability regarding information provided to the user by published literature or inside technical staff, its distributors and outside sales personnel. Errors in the catalog can occur and shall not create any liability whatsoever for HUMMEL AG or Sealcon LLC. All information provided is without guarantee and must be verified by the user.




Circular Connectors - M12 Power Benefits at a Glance


- Power Transmission to 16 A and 630 V
- Temperature rating to 257°F (125°C)
- Cable assembly and braid shielding in a single operation
- Field attachable and molded options
- Internationally proven quality - Conforms to Global Norm IEC 60112-2
- Unique protection against cable twisting



360 Degree Shielding
Guarantees Reliable
EMI (EMC) Protection




Max Cable
Diameter
0.43" (11 mm)




Industrial-suited
metal housing, also
available in stainless
steel




Circular Connectors - M12 Power Straight, Elbow & Panel Housing




Straight Connector, Female Thread			
Size	Part Number	Cable Ø	Coding
M12	SA7127 K1030 0000	.12 – .24" (3 – 6 mm)	K, L (for 5 contact positions)
M12	SA7127 K1040 0000	.20 – .35" (5 – 9 mm)	K, L (for 5 contact positions)
M12	SA7127 K1050 0000	.31 – .43" (8 – 11 mm)	K, L (for 5 contact positions)
M12	SA7127 S1030 0000	.12 – .24" (3 – 6 mm)	S, T (for 4 contact positions)
M12	SA7127 S1040 0000	.20 – .35" (5 – 9 mm)	S, T (for 4 contact positions)
M12	SA7127 S1050 0000	.31 – .43" (8 – 11 mm)	S, T (for 4 contact positions)




Straight Connector, Male Thread			
Size	Part Number	Cable Ø	Coding
M12	SA7127 K2030 0000	.12 – .24" (3 – 6 mm)	K, L (for 5 contact positions)
M12	SA7127 K2040 0000	.20 – .35" (5 – 9 mm)	K, L (for 5 contact positions)
M12	SA7127 K2050 0000	.31 – .43" (8 – 11 mm)	K, L (for 5 contact positions)
M12	SA7127 S2030 0000	.12 – .24" (3 – 6 mm)	S, T (for 4 contact positions)
M12	SA7127 S2040 0000	.20 – .35" (5 – 9 mm)	S, T (for 4 contact positions)
M12	SA7127 S2050 0000	.31 – .43" (8 – 11 mm)	S, T (for 4 contact positions)




Right Angle Elbow Connector, Female Thread			
Size	Part Number	Cable Ø	Coding
M12	SA7127 K3030 0000	.12 – .24" (3 – 6 mm)	K, L (for 5 contact positions)
M12	SA7127 K3040 0000	.20 – .35" (5 – 9 mm)	K, L (for 5 contact positions)
M12	SA7127 K3050 0000	.31 – .43" (8 – 11 mm)	K, L (for 5 contact positions)
M12	SA7127 S3030 0000	.12 – .24" (3 – 6 mm)	S, T (for 4 contact positions)




Right Angle Elbow Connector, Male Thread			
Size	Part Number	Cable Ø	Coding
M12	SA7127 K3130 0000	.11 – .23" (3 – 6 mm)	K, L (for 5 contact positions)
M12	SA7127 K3140 0000	.20 – .35" (5 – 9 mm)	K, L (for 5 contact positions)
M12	SA7127 K3150 0000	.31 – .43" (8 – 11 mm)	K, L (for 5 contact positions)




Panel Connector, w/ Flange		
Size	Part Number	Coding
M12	SA7127 K4000 0000	K, L (for 5 contact positions)
M12	SA7127 S4000 0000	S, T (for 4 contact positions)




Panel Connector, Front Mount, Single Hole (M16)		
Size	Part Number	Coding
M12	SA7127 K420 00000	K, L (for 5 contact positions)



Panel Connector, Rear Mount, Single Hole (PG 11)		
Size	Part Number	Coding
M12	SA7127 K5000 0000	K, L (for 5 contact positions)
M12	SA7127 S5000 0000	S, T (for 4 contact positions)



Panel Connector, Front Mount, Single Hole, Female Thread (M16)		
Size	Part Number	Coding
M12	SA7127 K4400 0000	K, L (for 5 contact positions)



Panel Connector, Front Mount, Single Hole, Female Thread (M20)		
Size	Part Number	Coding
M12	SA7127 K4410 0000	K, L (for 5 contact positions)
M12	SA7127 S4410 0000	S, T (for 4 contact positions)




Circular Connectors - M12 Power Molded Cordsets / Accessories




Straight Connector, Female Thread

Size	Cable Construction	Cable Jacket Options	Coding
M12	4G1,5	PUR or PVC	K, L, S, T
M12	4G1,5	Shielded / Unshielded	S, T
M12	5G0,75 / 5G1,5 / 5G2,5	Shielded / Unshielded	K, L





Straight Connector, Male Thread

Size	Cable Construction	Cable Jacket Options	Coding
M12	4G1,5	PUR or PVC	K, L, S, T
M12	4G1,5	Shielded / Unshielded	S, T
M12	5G0,75 / 5G1,5 / 5G2,5	Shielded / Unshielded	K, L




Right Angle Elbow Connector, Female Thread

Size	Cable Construction	Cable Jacket Options	Coding
M12	4G1,5	PUR or PVC	K, L, S, T
M12	4G1,5	Shielded / Unshielded	S, T
M12	5G0,75 / 5G1,5 / 5G2,5	Shielded / Unshielded	K, L



Right Angle Elbow Connector, Male Thread

Size	Cable Construction	Cable Jacket Options	Coding
M12	4G1,5	PUR or PVC	K, L, S, T
M12	4G1,5	Shielded / Unshielded	S, T
M12	5G0,75 / 5G1,5 / 5G2,5	Shielded / Unshielded	K, L



Plastic Protective Cap

Part Number	Type
SA7127 00098 0161	for connectors with Male Threads
SA7127 00098 0162	for connectors with Female Threads



Crimp Tool for Manual Crimping

Part Number	Type
S7000900908	for machined crimp contacts Signal connections M12, M16, and M23



Brass Protective Cap

Part Number	Type
SA7127 01090 0163	for connectors with Female Threads



Brass Protective Cap

Part Number	Type
SA7127 00090 0162	for connectors with Male Threads



Brass Protective Cap with Chain

Part Number	Type
SA7127 01095 0705	for connectors with Female Threads Length 70 mm




Brass Protective Cap with Chain

Part Number	Type
SA7127 01095 0704	for connectors with Male Threads Length 70 mm



Circular Connectors - M12 Power Contacts / Inserts


Contacts



Contacts - Pin

* Upon Request


Part Number	Crimp Range	AWG	Type
SA7127 01090 1521*	0.75 mm ²	18	Crimp pin 1.5 mm, machined
SA7127 01090 1531	1.50 mm ²	16	Crimp pin 1.5 mm, machined



Contacts - Socket

* Upon Request

Part Number	Crimp Range	AWG	Type
SA7127 01090 1522*	0.75 mm ²	18	Crimp socket 1.5 mm, machined
SA7127 01090 1532	1.50 mm ²	16	Crimp socket 1.5 mm, machined
SA7127 01090 1542	2.50 mm ²	14	Crimp socket 1.5 mm, machined



Contacts - Socket


Part Number	Crimp Range	AWG	Type
SA7127 01091 1522*	0.75 mm ²	18	Crimp socket 1.5 mm, machined PE
SA7127 01091 1532	1.50 mm ²	16	Crimp socket 1.5 mm, machined PE
SA7127 01091 1542	2.50 mm ²	14	Crimp socket 1.5 mm, machined PE

* Upon Request

Crimp Tool Settings for Crimp Tool (Crimp Tool S7000900908)


Part Number	Crimp Contact	Cross Section (mm ²)	AWG	Crimp Tool Setting	Locator Setting
SA7127 01090 1531	Crimp pin 1.5 mm	1.5	16	1.45	P1
SA7127 01090 1541	Crimp pin 1.5 mm	2.5	14	1.70	P1
SA7127 01090 1532	Crimp socket 1.5 mm	1.5	16	1.45	P2
SA7127 01090 1542	Crimp socket 1.5 mm	2.5	14	1.70	P2
SA7127 01091 1532	Crimp socket 1.5 mm PE	1.5	16	1.45	P3
SA7127 01091 1542	Crimp socket 1.5 mm PE	2.5	14	1.70	P3

Inserts




Inserts K (Crimp)

Part Number	Type
SA7127 K0394 1101	Crimp insert, pins, 4 + PE without contacts Required contacts: 4 x pins, 1 x socket PE
SA7127 K0394 1102	Crimp insert, sockets, 4 + PE without contacts Required contacts: 4 x sockets, 1 x pin PE




Inserts L (Crimp)

Part Number	Type
SA7127 L0394 1101	Crimp insert, pins, 4 + PE without contacts Required contacts: 4 x pins, 1 x socket PE
SA7127 L0394 1102	Crimp insert, sockets, 4 + PE without contacts Required contacts: 4 x sockets, 1 x pin PE



Inserts S (Screw)

Part Number	Type
SA7127 S0593 1101	Crimp pin 3 + PE contacts with screw termination
SA7127 S0593 1102	Crimp socket 3 + PE contacts with screw termination



Inserts T (Screw)


Part Number	Type
SA7127 T0590 4101	Crimp pin 4-pole contacts with screw termination
SA7127 T0590 4102	Crimp socket 4-pole contacts with screw termination



Circular Connectors - M12 Power

Assembly Instructions - Straight Connector


Straight Connector Female / Male Thread, K- / L-Coding (Crimp)





Circular Connectors - M12 Power Assembly Instructions - Panel Connector

Panel Connector, K- / L-Coding (Crimp)






Circular Connectors - M12 Power

Hummel / Jaeger - M8, M12, M16, M23, M27, M40

Circular Connector - Overview



M12 Power

Signal Connectors

M40

M27

CIRCULAR CONNECTORS

M23

PROFINET (PoE)

M23 Hybrid

Power Connectors

Twintus

M8

M12


Twilock

M23 RJ45

Molded Cordsets

M16

JAEGER



Request Your Current Catalog Today!



Other catalogs & flyers available. Call for details...

Further information on the products presented here and everything else Sealcon has to offer can be found on our website:

www.sealconusa.com



Setting Standards

Our website is consistently updated. Sealcon catalogs are also available for download online.



SEALCON

7374 S. Eagle Street Centennial, CO 80112 USA
Toll Free: 800-456-9012 / 303-699-1135
Fax: 303-680-5344
Email: info@sealconusa.com
Web: www.sealconusa.com